

FS-720 Specifications

BASIC SPECIFICATIONS:

| | |
|--------------------------|--|
| Configuration: | Desktop Monochrome Printer with Standard 250 Sheet Drawer plus Single Sheet Multi-Purpose Tray |
| Resolution: | 600 x 600 dpi |
| Printer Memory: | Standard / Max 8MB |
| Electrical Requirements: | 120V, 60Hz, 6.8A |
| Dimensions: | 15.0"W x 15.4"D x 9.6"H |
| Weight: | 20.3 lbs |
| Max Duty Cycle: | 12,000 Pages per month |

CONTROLLER SPECIFICATIONS:

| | |
|-----------------------------|---|
| Controller: | 32bit RISC |
| Supported PDL / Emulations: | Kyocera Mita Advanced Data Stream (KMADS) |
| Windows OS Compatibility: | Windows 98SE/Me/NT4.x/2000/XP |
| Connectivity / Interface: | Full-Speed USB 2.0 |
| Expansion | Optional IB-100 External Print Server |
| Driver: | Host Based |

OUTPUT SPEEDS:

| | |
|-------------------|------------------------------|
| Warm-Up Time: | Less than 16 Seconds |
| First Print Out: | Less than 11 Seconds |
| Pages Per Minute: | 17 Letter / 16 A4 / 15 Legal |

PAPER SUPPLY:

| | |
|-------------------------|---|
| Standard Paper Sources: | 250 Sheet Drawer, Single Sheet MPT |
| Drawer Paper Size: | 8.5" x 11", 8.5" x 13", 8.5" x 14", A4, B5, A5 |
| MPT Paper Size: | 8.5" x 11", 8.5" x 13", 8.5" x 14", A4, B5, A5, Custom (2.8" x 5.8" - 8.5" x 14") |
| Paper Capacity: | 251 Sheets |
| Paper Weight: | 16-28 lb Bond via Paper Drawer, 16 lb Bond - 90 lb Index via MPT |
| Input Materials: | Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes |

CONSUMABLES:

| | |
|----------|--|
| TK-112E: | 2,000 pages @ 5% Coverage |
| | * Ships with 3,000 pages @ 5% Coverage. ISO/IEC 19752 Compliant. |



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2005 Kyocera Mita America, Inc.
www.kyoceramita.com/us

