

FS-C5020N Specifications

basic specifications:

Configuration:	Color Tandem Network Printer with Standard 500 Sheet Drawer, 100 Sheet Multi-Purpose Tray. Optional Duplexing, Additional Paper Drawers and HDD.
Resolution:	600 x 600 DPI (Multi-bit)
Printer Memory:	Standard 128MB, Upgradeable to 1024MB via 100 Pin DDR DIMMs, Standard CF Card Slot. (Type 1) Optional HDD
Electrical Requirements:	120V, 60Hz, 9.1A
Dimensions:	13.6"W x 18.5"D x 15.2"H
Weight:	48.6 lbs
Max Duty Cycle:	85,000 pages per month

controller specifications:

CPU/MHz:	Embedded PowerPC750CXR/ 400 MHz Controller
Supported PDL / Emulations:	PRESCRIBE, KPDL3 (PS3), PCL 6 (PCL 5c, PCL XL)
Fonts:	136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font
Windows™ OS Compatibility:	Windows™ 95/98/Me/2000/XP
Novell™ OS Compatibility:	Novell NetWare™ 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100 BaseTX, Hi-Speed USB 2.0, Bi-Directional Parallel IEEE1284 (Nibble/ECP)
KUIO LV Expansion Slot (1):	Optional IB-11: Serial RS-232C; IB-20: 10/100 BaseTX, 10Base2; IB-22: Enhanced Wireless NIC; or Hard Disk Drive
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/Unix, Certified Uni Driver
Utilities:	KM-NET Viewer, KM-NET Client, PDF Direct Print, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

output speeds:

Warm-Up Time:	Within 80 Seconds
First Print Out Color:	16.0 Seconds
First Print Out Monochrome:	16.0 Seconds
Pages Per Minute (Color / Mono):	17 / 17 Letter, 16 / 16 A4, 14 / 14 Legal

paper supply:

Standard Paper Sources:	500 Sheet Drawer, 100 Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
MPT Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5, Custom (2.8" x 5.8" - 8.5" x 14")
Min / Max Paper Capacity:	600 / 2,100 Sheets
Paper Weight:	16 - 28 lb Bond via Paper Drawers, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes

paper handling options:

duplex unit: DU-301

Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
Paper Weight:	16 - 28 lb Bond
Dimensions / Weight:	13.6"W x 22"D x 9.7"H / 12.3 lbs

paper drawer: PF-60

Paper Capacity:	500 Sheets
Max. Drawers:	3 Drawers
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
Dimensions / Weight:	13.6"W x 17.8"D x 4.1"H / 8.4 lbs

envelope feeder: EF-60

Envelope Capacity:	1.5" Height Capacity
--------------------	----------------------

face-up tray: PT-300

Paper Capacity:	250 sheets for printer, 100 sheets for Duplexer (DU-301)
-----------------	---

options:

hard disk drive:

Enables Document Printing and e-MPS Functions:
Private Print, Job Storage, Quick Copy, Proof and Hold, Virtual MailBoxes

consumables:

TK-512K:	Black Toner* 8,000 Pages @ 5% Coverage*
TK-512Y:	Yellow Toner* 8,000 Pages @ 5% Coverage*
TK-512M:	Magenta Toner* 8,000 Pages @ 5% Coverage*
TK-512C:	Cyan Toner* 8,000 Pages @ 5% Coverage* * ships with 4,000 Pages @ 5% Coverage



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2005 Kyocera Mita America, Inc.
www.kyoceramita.com/us

